## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Gem Imports Ltd

Supplier's address: Gem Imports Ltd, 2 Athena Way, Hoyland, Barnsley, S74 0FQ

Model identifier: ELE8121/OB

Type of light source:

| //*** 8                                     |                    |                 |                                   |                   |
|---|--------------------|-----------------|-----------------------------------|-------------------|
| Lighting technology used:                   |                    | LED             | Non-directional or directional:   | NDLS              |
| Light source cap-type                       |                    | B22             |                                   |                   |
| (or other electric i                        |                    |                 |                                   |                   |
| Mains or non-mains:                         |                    | MLS             | Connected light                   | No                |
|   |                    |                 | source (CLS):                     |                   |
| Colour-tuneable light source:               |                    | No              | Envelope:                         | -                 |
| High luminance light source:                |                    | No              |                                   |                   |
| Anti-glare shield:                          |                    | No              | Dimmable:                         | No                |
|   |                    | Product para    | ameters                           |                   |
| Parameter                                   |                    | Value           | Parameter                         | Value             |
|   |                    | General product |                                   |                   |
| Energy consump                              | ition in on-       | 5               | Energy efficiency class           | F                 |
| mode (kWh/1000                              |                    | 3               | Energy energy class               |                   |
| to the nearest inte                         |                    |                 |                                   |                   |
| Useful luminous fl                          |                    | 470 in          | Correlated colour                 | 4,000             |
| dicating if it refers                       |                    | Sphere (360°)   | temperature, rounded to           | ,                 |
|   | a wide cone (120º) |                 | the near- est 100 K, or           |                   |
| or in a narrow cor                          |                    |                 | the range of correlat-            |                   |
|   | ie (90-)           |                 | •                                 |                   |
|   |                    |                 | ed colour temper-                 |                   |
|   |                    |                 | atures, rounded to the            |                   |
|   |                    |                 | nearest 100 K, that can           |                   |
|   |                    |                 | be set                            |                   |
| On-mode power (P <sub>on</sub> ), ex-       |                    | 5.0             | Standby power (P <sub>sb</sub> ), | 0.00              |
| pressed in W                                |                    |                 | expressed in W and                |                   |
|   |                    |                 | rounded to the sec-               |                   |
|   |                    |                 | ond decimal                       |                   |
| Networked standby power (P <sub>net</sub> ) |                    | -               | Colour rendering in- dex,         | 80                |
| for CLS, expressed in W and                 |                    |                 | rounded to the nearest            |                   |
| rounded to the second dec- imal             |                    |                 | integer, or the range of          |                   |
|   |                    |                 | CRI-val- ues that can be          |                   |
| Outer dimen-                                | Height             | 110             | Spectral power dis-               | See image in last |
| sions without                               | Width              | 60              | tribution in the                  | page              |
| separate con-                               | Depth              | 60              | range 250 nm to 800 nm,           |                   |
| trol gear, light-                           | Ceptin             | 00              | at full-load                      |                   |
| ing control                                 |                    |                 |                                   |                   |
| parts and non-                              |                    |                 |                                   |                   |
| lighting con-trol                           |                    |                 |                                   |                   |
| parts, if any                               |                    |                 |                                   |                   |
| (millime- tre)                              |                    |                 |                                   |                   |
| Claim of equivalent power <sup>(a)</sup>    |                    | Yes             | If yes, equivalent                | 40                |
|   |                    |                 | power (W)                         |                   |
|   |                    |                 | Chromaticity coordi-              | 0,380             |
|   |                    |                 | nates (x and y)                   | 0,380             |
|   |                    |                 |                                   | 0,500             |

| Parameters for LED and OLED light sources:   |            |  |      |  |  |
|--|------------|--|------|--|--|
| R9 colour rendering index value  | 0          | Survival factor                          | 0.90 |  |  |
| the lumen maintenance factor   | 0.95       |  |      |  |  |
| Parameters for LED and OLED mains light  | t sources: | · · ·                                    |      |  |  |
| displacement factor (cos φ1)   | 0.00       | Colour consistency in<br>McAdam ellipses | 6    |  |  |
| Claims that an LED light source<br>replaces a fluorescent light<br>source without integrated bal-last of<br>a particular wattage | _(b)       | If yes then replace-<br>ment claim (W)   | -    |  |  |
| Flicker metric (Pst LM)  | 1.0        | Stroboscopic effect<br>metric (SVM)      | 0.9  |  |  |

<sup>(a)</sup>'-' : not applicable;

<sup>(b)</sup>'-' : not applicable;